



The Single Point, Wide-Coverage Solution



AW650
6 1/2" 2-Way
Indoor / Outdoor
Stereo Pair
Black or White



AW525
5 1/4" 2-Way
Indoor / Outdoor
Stereo Pair
Black or White



AW400
4" 2-Way
Indoor / Outdoor
Stereo Pair
Black or White

Listening to music outdoors and in large interior spaces has always been a problem. When you move off-center, you miss critical information. But we've solved all that. With just one Proficient AW600TT, you get even coverage throughout the listening area.

In a word, they're unique. This twin tweeter speaker masters the challenges of big, open spaces with super-wide coverage and a degree of dispersion that conventional stereo speaker systems can't match. We call it "constant directivity". You'll call it amazing.

Thanks to twin tweeter technology, the high frequencies really carry over long distances, and provide enhanced high-frequency dispersion. Plus, with a dual voice coil woofer, the AW600TT really cranks out the bass, even at low listening levels.

For stereo environments and near-field listening applications, the AW650, AW525 and AW400 speakers are excellent - inside and out - providing superb imaging and staging across the sound field.

AW Series speakers are built to last, too. They'll take the heat - and the cold - for years to come.

Quality-built, of course. Exactly what you'd expect from a premium brand like Proficient.

PROFICIENT[™]
Audio Systems

proficientaudio.com



AW600TTblk/wht



AW500TTblk/wht

Description	Single Point, Dual Voice Coil, Twin Tweeter Speaker	Single Point, Dual Voice Coil, Twin Tweeter Speaker
Wiring	Four Conductor (Left and Right)	Four Conductor (Left and Right)
Unit of Measure	Each	Each
Brackets	Included	Included
Woofer Size	6½"	5¼"
Woofer	Polypropylene Cone with Dual Voice Coil and Butyl Rubber Surround	Polypropylene Cone with Dual Voice Coil and Butyl Rubber Surround
Tweeters	Two 1" Supernil Soft Dome	Two 1" Supernil Soft Dome
Pivoting Tweeters	Yes	Yes
Power Handling	150 Watts	100 Watts
Freq Response	35Hz-20kHz	38Hz-20kHz
Sensitivity	91dB	89dB
Impedance	4 ohms	4 ohms
Dimensions (H x W x D)	12" x 7" x 8"	11" x 7" x 6¼"
Warranty	10-Year Limited	10-Year Limited



AW650blk/wht



AW525blk/wht



AW400blk/wht

Description	6½" Two Way Indoor / Outdoor Speakers	5¼" Two Way Indoor / Outdoor Speakers	4" Two Way Indoor / Outdoor Speakers
Wiring	Left: 2 Conductor Right: 2 Conductor	Left: 2 Conductor Right: 2 Conductor	Left: 2 Conductor Right: 2 Conductor
Unit of Measure	Pair	Pair	Pair
Brackets	Included	Included	Included
Woofer Size	6½"	5¼"	4"
Woofer	Polypropylene Cone with Butyl Rubber Surround	Polypropylene Cone with Butyl Rubber Surround	Polypropylene Cone with Butyl Rubber Surround
Tweeter	1" Supernil Soft Dome	1" Supernil Soft Dome	¾" Supernil Soft Dome
Pivoting Tweeter	Yes	Yes	No
Power Handling	150 Watts	125 Watts	100 Watts
Freq Response	37Hz-20kHz	45Hz-20kHz	55Hz-20kHz
Sensitivity	89dB	88dB	87dB
Impedance	8 ohms	8 ohms	8 ohms
Dimensions (H x W x D)	11" x 7" x 6¼"	9¾" x 6½" x 6¾"	7¾" x 5½" x 5½"
Warranty	10-Year Limited	10-Year Limited	10-Year Limited